

FIELD REPORT FOR CEMENTING OF WELLS

APPROVED CASTING PROGRAM

Casing Data:

Inspected by L. A. Gilmer date 6-28-74

Size of hole // " Size of Casing 8 7/8 Sacks cement required

Type of Shoe used Inside Float collar used Insert Btm 2 its welded Thru Holes

TD of hole 1300 Set 2900 Feet of 8 3/4 Inch 24 # Grade

New-used csg. @ 1296 GL with 150 sacks neat cement around shed 2% cc 17.5
+ 550 sax 2000 L/ft water additives 4 1/2 10 1/2 1/2 5 1/2 Gilsonite 2% cc 12.8

Plug down @ 2116 ~~(AM)~~ (PM) Date 6-29-74

Cement circulated None No. of Sacks None

Cemented by Daniel Witnessed by G. J. McNamee

Temp. Survey ran @ 8.10 (~~PM~~) (P.M.) Date 6-25-74 Top cement @ 260'

[illegible]

Method Used	Witnessed by
-------------	--------------

Checked for shut off @ (AM) (PM) Date

Method used _____ Witnessed by _____

Remarks: S. 200 7D 320 K13 12 3/4" PD 1613. P-1 Date 2/5/54

1"6 790 Ent 96/SX China 20 CC Line 10/SX

Two Receipts 446