

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NA-4026

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ Drilling Well	SEP 25 1974
2. NAME OF OPERATOR David Fasken ✓	
3. ADDRESS OF OPERATOR 608 First National Bank Building, Midland, Texas 79701	O. C. C. OFFICE
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1300' FWL & 1300' FSL, Sec. 29, T-20-S, R-25-E	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3592' K.B.

7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Howell "29" Federal
9. WELL NO. 1
10. FIELD AND POOL, OR WILDCAT Cemetery Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29, T-20-S, R-25-E
12. COUNTY OR PARISH Eddy
13. STATE New Mexico

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)			

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
(Other) Cementing Surf. & Inter. Csg.	☒		

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Spudded at 4:30 p.m., September 4, 1974.
- Drilled 17 1/4" hole to 240'.
- Ran 7 jts. (245.86') 13-3/8", H-40 casing, set at 240'. Cemented w/150 sxs. Halliburton-Lite w/2 1/2% CaCl & 1 1/2# flocele/sack, and 100 sxs. Class "C" w/2 1/2% CaCl & 1 1/2# flocele/sack. Circulated excess of 100 sxs. Plug down @ 7:15 a.m., 9-5-74.
- W.O.C. 18 hours.
- Drilled 12 1/4" hole to 3215' on September 12, 1974.
- Ran 18 jts. (725.88') 8-5/8", 32#/ft., J-55 & 57 jts. (2479.24') 8-5/8", 24#/ft., J-55, set @ 3215', cemented w/1000 sxs. Halliburton Lite with 1 1/2# flocele/sx. and 2 1/2% CaCl (12.7#/gal.), and 200 sxs. Class "C" w/2 1/2% CaCl (14.8#/gal.). Circulated excess of 229 sxs. Plug down at 3 p.m., C.D.T., 9-13-74. Cemented by Mr. Don Gordon, U.S.G.S.
- W.O.C. 24 1/2 hours.
- Drilling ahead with 7-7/8" bit.

SEP 23 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

Robert H. Angevine

SIGNED

TITLE

Agent

DATE


9-20-74

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE



*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.