

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM-4025

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cemetery Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Cemetery (Morrow)

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 21, T-20-S, R-25-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to different reservoirs.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

JAN 23 1975

2. NAME OF OPERATOR

David Fasken /

3. ADDRESS OF OPERATOR

608 First Natl. Bank Bldg., Midland, Texas 79701

O. C. C.
ARTESIA, OFFICE4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3505' K.B.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

FULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) complete for production

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

XX

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 12-7-74 Tested 4½" casing to 3000 psig - held OK, ran GR collar log from 9619' up to 8400', set Otis 4½" W.B. packer @ 9000'.
- 12-10-74 Ran Otis "J" Latch Seal Assembly on 291 jts. of 2-3/8", N-80, buttress thread tubing - landed in packer at 9000'.
- 12-11-74 Perforated from 9448' to 9452' w/5 jets, 9474-9482' w/5 jets, and 9550-54' w/5 jets, all 0.24" dia. entry hole.
- 12-12-74 thru 12-16-74 Flowed well intermittently to clean up on a 3/8" choke, F.T.P. 1245 psig, rate - 4277 MCF per day.
- 12-18-74 S.I.T.P. 2960 psig, C.A.O.F.P. 5,800 MCF per day
- 12-19-74 Shut in waiting on pipeline connection.

RECEIVED

JAN 20 1975

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

Robert H. Angevine

SIGNED

TITLE

Agent

DATE 1-16-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side