

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARRESTIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Hondo Dry Co.		Lease Osage Bayd Com.		Well # 1	
Location of Well	Unit 9804 660W	Section 15	Township 19	Range 25	County Eddy
Drilling Contractor Hondo & Co.			Type of Equipment Rotary T-Start 9-10-74		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 7/8"	48		500	500 cins.
11	8 7/8"	24		1300	400 cins.
7 7/8"	5 1/2	17+20		9400	350

Casing Data:

Surface 37 joints of 8 7/8 inch 24 # Grade API N-40 K-55
(Approved) (Rejected)

Inspected by J. A. Mcmurry date 10-1-74

Cementing Program

Size of hole 12 1/2 to 800' Size of Casing 8 7/8 Sacks cement required 500

Type of Shoe used Guide Float collar used Insert Btm 3 jts welded Thread Lock

TD of hole 1150' KB Set 1136' Feet of 8 7/8 Inch 24 # Grade K-55

New-used csg. @ 1136' with 200 sacks neat cement around shoe Class C 2% cc 14.5
+ 300 sax Fluoride additives 5* Silicate 1/4" Flocc 2% cc 13.0

Plug down @ 10:40 (AM) (PM) Date 10-1-74

Cement circulated Yes No. of Sacks 200/56

Cemented by Wallington Witnessed by J. A. Mcmurry

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Surface 17 1/2" hole TD 404' KB Set 390' GL 10 1/2

13 3/8" New 48# API H-40 Cnt 400/sx Class C 2% cc

PD 5:00 PM 9-29-74 Cinc.