			ر ال	1
Submit 3 Copies To Appropriate District State of New Mexico			Form C-103	
Office District I Energy, Minerals and Natural Resources			1	Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.	1
District II 811 South First, Artesia, NM 88210 OIL CONSERVATION DIVISION			30-015-21423	
District III 1220 South St. Francis Dr.			5. Indicate Type of STATE	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505			6. State Oil & G	
1220 S. St. Francis Dr., Santa Fe, NM 87505			VA-1377	
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or	Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			Avenger AVG State	
PROPOSALS.) 1. Type of Well:			J	
Oil Well Gas Well X	Other			
2. Name of Operator			7. Well No.	
Yates Petroleum Corporation			#1	
3. Address of Operator			8. Pool name or Wildcat	
105 S. 4 th Street Artesia, NM 88210			Undes. Dagger Draw Upper Penn, South Assoc.	
4. Well Location				
TT 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	990 fort from the South	1ing and 1000	fact from the W	est line
Unit Letter K: I	980 feet from the South	inie and	_ reet from the	esi mie
Section 32	Township 20S Range	24 E N	MPM Eddy	County
	10. Elevation (Show whether I	OR, RKB, RT, GR, e	tc.)	
		3' GR	D 0:1	
	ppropriate Box to Indicate 1			
NOTICE OF IN	TENTION TO:	SUE	BSEQUENT REI	ALTERING
PERFORM REMEDIAL WORK	PLUG AND ABANDON		CASING CASING	
TEMPORARILY ABANDON	CHANGE PLANS MULTIPLE		COMMENCE DRILLING OPNS. X ABANDONMENT CASING TEST AND	
PULL OR ALTER CASING	COMPLETION	CEMENT JOB		
OTHER:		OTHER:		
Describe proposed or completed op starting any proposed work). SEE I recompilation.				
4/19/00 - MIRU pulling unit. Di	rilled out 20' surface plug.			
4/20/00 - Drill out plugs 1945-2		H to 8630'. No pl	ug at 5750'.	
4/21/00 – Run open hole logs				
4/22/00 – Wash down to 9105		23.464		
4/23/00 – Run 215 joints (9113 55 joints 5-1/2" 17# J 55 (229		JWS.		
157 joints 5-1/2" 15.5# J 55 (
3 joints 5-1/2" 17# J 55 (125.				
Float shoe set at 9103'. Float				
945 sxs Super C + .5% FL52 + .5	5%Fl25 + 5 pps gilsonite (yld	1.65, wt 13.2) PD	at 9:00 PM. Bum	ped plug to 2575#,
held OK. Circ 113 sxs.				
I hereby certify that the information	above is true and complete to th	e best of my knowle	edge and belief.	
SIGNATURE ASSET	TITLE _	Engineering Tea	chnician DATE	February 26, 2002
Type or print name Susan He	7			No. 505-748-1471
(This space for State use)	W		*	<u>.</u>
0 '				MR - 4 2002
APPPROVED BY Conditions of approval, if any:	enly TITLE			DATE