

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-015-21423

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

VA-1377

7. Lease Name or Unit Agreement Name:

Avenger AVG State

7. Well No.

#1

8. Pool name or Wildcat

Undes. Dagger Draw Upper Penn, South Assoc.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter **K** : **1980** feet from the **South** line and **1980** feet from the **West** line

Section **32** Township **20S** Range **24E** NMPM **Eddy** County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3863' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: perforate, acidize and frac ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/1/00 - Perforate Morrow 8845-8853', 36 holes; 8866-8873', 32 holes; 8912-8916', 20 holes; total of 88 holes, .42".

5/2/00 - Acidize perms 8845-8916' with 1500 gals 7.5% Morrow acid.

5/4/00 - Set CIBP at 8800', cap with 35' cement.

Perforate Strawn 8202-8210' with 36 holes, .42". Acidize with 750 gals 7.5% Morrow acid.

5/9/00 - Rig down pulling unit, waiting on frac date.

5/19/00 - Frac Strawn perms with 12,000 gals 40# gel + 2100 gals methanol 70Q CO2 foamed carrying 30,000# 20/40 AcFrac Black sand.

5/31/00 - Perforate Strawn 8066-8070' with 5 holes, .42". Acidized with 1500 gals 15% IC HCL.

6/5/00 - Perforate Penn lime 7504-7516' with 13 holes, .42". Acidize with 1000 gals 15% IC HCL.

6/7/00 - Perforate Penn lime 7429-7436', 8 holes; 7532-7542', 11 holes; 7552-7558', 7 holes; 7620-7626', 7 holes; total of 33 holes, .42".

See Attached

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Engineering Technician DATE **February 26, 2002**

Type or print name

Susan Herpin

Telephone No. **505-748-1471**

(This space for State use)

APPROVED BY

TITLE

DATE

Conditions of approval, if any:

MAR - 4 2002

Yates Petroleum Corporation
Avenger AVG State #1
API – 30-015-21423
Section 32 T20S-R24E
Eddy County, NM

Describe proposed or completed operations: (continued)

6/7/00 – Acidized perfs 7620-7626' with 1000 gals 15% IC HCL.

6/9/00 - Acidized perfs 7504-7558' with 2000 gals 15% IC HCL.

Acidize perfs 7429-7436' with 1000 gals 15% IC HCL.

6/10-6/12/00 – Straddle perfs 7429-7626'. Set RBP at 7697' and packer at 7389'. Swab test.

6/13/00 – Rig down and release all equipment. Well is SI.