

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION
 3-NMOCC-Artesia
 1-File
 2-Mesa Petr., GIHLS TOWER, Suite 904
 Midland, Texas 79701

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	K-6096

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	RECEIVED		7. Unit Agreement Name
2. Name of Operator GETTY OIL COMPANY	MAR 12 1975		8. Farm or Lease Name STATE K 6096 A
3. Address of Operator P.O. BOX 249, HOBBS, NEW MEXICO			9. Well No. 1
4. Location of Well UNIT LETTER <u>N</u> <u>1980</u> FEET FROM THE <u>WEST</u> <u>ARTESIA, OFFICE</u> LINE AND <u>860</u> FEET FROM THE <u>SOUTH</u> LINE, SECTION <u>28</u> TOWNSHIP <u>19-S</u> RANGE <u>25-E</u> NMPM.			10. Field and Pool, or Wildcat UNDESIGNATED (MORROW)
15. Elevation (Show whether DF, RT, GR, etc.) 3488.7 GR			12. County EDDY

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12-1/4" hole to 1300'. Set 9-5/8" 36 and 40# K-55 Casing at 1298'. Cemented with 280 sacks Class "C" with 2% A-2 and 4% Gel and 2% Cacl and 1/4# flocele and 5# Gilsonite per sack, and 200 sacks Class "C" with 2% Cacl. Circulated estimated 190 sacks cement. Waited on cement 24 hours. Tested 9-5/8" casing with 2000# for 30 minutes, no drop in pressure.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY

SIGNED C.L. Wade: C. L. Wade

TITLE AREA SUPERINTENDENT

DATE 3-10-75

APPROVED BY [Signature]

TITLE SUPERVISOR, DISTRICT II

DATE MAR 12 1975

CONDITIONS OF APPROVAL, IF ANY:

WLG/bh