

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 30 days after the completion of any newly-initiated geologic well. It shall be accompanied by one copy of all electrical and radio-activity logs from the well and a summary of all logs and tests conducted, including data from tests. All depths reported shall be measured in feet in the case of directionally drilled wells; true vertical depth shall also be reported. For multiple completions, tests of through 34 shall be reported for each zone. The form is to be filed in quadruplicate except in state lands, where six copies are required. See Rule 1135.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____ 7956	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Qizte _____
T. Glorieta _____ 2233	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Padlock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinberry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____ 3553	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____ 6057	T. Morrow _____ 8970	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____ 7578	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	472	472	Surface and Redbeds	9252	9332	80	Shale, Chert
472	1123	650	Anhydrite	9332	9410	78	Shale
1123	1225	97	Anhydrite, Sand				
1225	1470	245	Anhydrite				
1470	1769	299	Lime				
1769	2269	500	Lime-Dolomite				
2269	5535	3266	Lime				
5535	5714	179	Lime & Shale				
5714	6274	560	Lime				
6274	6990	716	Lime and Shale				
6990	7610	620	Shale				
7610	7704	94	Lime & Shale				
7704	7712	8	Shale				
7712	8030	318	Lime & Shale				
8030	8164	134	Dolomite & Shale				
8164	8300	136	Dolomite				
8300	8372	72	Dolomite & Lime				
8372	8383	11	Dolomite				
8383	8433	50	Dolomite & Shale				