

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>C. H. Juri</u>		Lease <u>Bossett</u>		Well # <u>1</u>	
Location of Well	Unit <u>1805</u> <u>660C</u>	Section <u>20</u>	Township <u>20</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	Type of Equipment <u>Cable tools to start 5-25-75</u>				

APPROVED CASING PROGRAM CABLE TOOL

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11 7/8"</u>	<u>8 7/8"</u>	<u>24-28</u>		<u>300</u>	<u>circ.</u>
<u>6 1/2"</u>	<u>4 1/2"</u>	<u>9.5</u>		<u>1300</u>	<u>circ.</u>

Casing Data:

Surface 17 joints of 8 1/8 inch 28 # Grade? USED

(Approved) (~~Rejected~~)

Inspected by Leon Benjatin date 6-3-75

Cementing Program

Size of hole 11 Size of Casing 8 1/8 Sacks cement required 72 04/5

Type of Shoe used GUIDE Float collar used No Btm 3 jts welded No

TD of hole 2856L Set 289' Feet of 8 1/8 Inch 28 # Grade? USED

New-used csg. @ 2856L with 75 sacks neat cement around shoe

+ — sax — additives 2% PAC-1

Plug down @ 110 (AM) (PM) Date 6-3-75

Cement circulated NO No. of Sacks

Cemented by Howco Witnessed by Leon Benjatin

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Plan to fill outside of 8 1/8" w/ PER GRAVILL READY-MIX TO SURFACE