

Drawer B9
Artesia, NM 88210

CONTACT RECEIVED
OFFICE FOR NUM
OF COPIES REQUIRED
(Other instructions on re-
verse side)

BLM Roswell District
Modified Form No.
NM060-3160-4

Form 3160-5
(July 1989)
(Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OCT 17 '89

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> RECOMPLETION		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR YATES PETROLEUM CORPORATION /		8. FARM OR LEASE NAME Ross EG Federal Com	
3. ADDRESS OF OPERATOR 105 South 4th St., Artesia, NM 88210		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL & 1980' FWL, Sec. 20-19S-25E		10. FIELD AND POOL, OR WILDCAT Undes. North Dagger Draw-Upper Penn	
14. PERMIT NO. 30-015-21523		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3563' KB	
11. SEC., T., R., M., OR BLK. AND SURVEY OR ARMA Unit K, Sec. 20-T19S-R25E		12. COUNTY OR PARISH Eddy	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Plugback, perforate, treat

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

9-26-89. Set CIBP 8190' w/35' cement cap. Perforated 7798-7841' w/14 .42" holes as follows: 7798, 99, 7804, 27, 29, 31, 32, 33, 34, 35, 36, 39, 40, and 7841'. Acidized perforations 7798-7841' w/3500 gals 20% NEFE acid with one drum scale and one drum corrosion inhibitor.

Post ID-2
11-3-89
P&H S&H

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Production Supervisor

DATE 10-9-89

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

OCT 13 1989

*See Instructions on Reverse Side

SJS
CARLSBAD, NEW MEXICO