

N. M. O. C. C. COPY

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
7051

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
R S Federal

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA
Sec. 25, T20S, R24E

12. COUNTY OR PARISH
Eddy

13. STATE
N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

JUL 29 1975

O. C. C.
ARTESIA, OFFICE

1. OIL WELL GAS WELL OTHER Dry Hole

2. NAME OF OPERATOR

Coquina Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Drawer 2960, Midland, TX. 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface
1980' FWL & 660' FNL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

G.L. 3606

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Progress report

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Drilled a 12 1/4" hole to 2490'. Ran 59 jts. 8 5/8" 24# K-55 8rd STC casing and set at
2491'. Cemented with 1000 sacks Lite Wate with 3# gilsonite, followed by 200 sacks
Class C with 2% calcium chloride and 1/4# Flocele in all cement. Circulated 200
sacks to surface. Pumped plug down with 160 B_W at 9:30 PM, June 21, 1975. W.O.C.
18 hrs. Drilled a 7 7/8" hole to T. D. of 9810'. Logs and DST's indicated no
commercial production. Prep to plug and abandon.

RECEIVED
JUL 28 1975
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Duane C. Radtke

TITLE Engineer

DATE 7-25-75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

JUL 28 1975

H. L. BEEKMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side