

SUPPLEMENTAL DRILLING DATA

MCKAY OIL CORPORATION
Charolette McKay Federal #3
NE/4NW/4 of Sec. 25, T-20S, R-24E
Eddy County, New Mexico
NM-34647

RECEIVED
AUG 7 12 00 PM '91
CAG
ARE

The following items supplement Form 9-331C in accordance with instruction contained in NTL-6.

1. SURFACE FORMATION: Queen Formation

2. ESTIMATED TOPS OF GEOLOGICAL MARKERS:

San Andres	-	664'
Glorietta	-	2270'
Tubb	-	2989'
Bone Springs	-	3248'
Wolfcamp	-	6170'
Canyon Lime	-	7563'
Canyon Dol.	-	7750'

3. ESTIMATED DEPTHS TO WATER, OIL OR GAS FORMATION:

Fresh Water	-	Approximately 400'
Oil	-	In Canyon formation below 7,800'

4. PROPOSED CASING PROGRAM: Original Bore hole 7 7/8".
Existing casing - 13 3/8" (48#) set to 307' circulated.
8 5/8" (24#) set at 2,491' with 1,200 SX circulated.
5 1/2" production casing.

5. PRESSURE CONTROL EQUIPMENT: Blowout preventer
will consist of 10" - 900 Series with 3,000#WP
3,000# test pressure double ram system.
A sketch of the BOP is attached.

6. CIRCULATING MEDIUM:
Fresh Water to 7,000, then change to fresh water
gel to 8,100'.

7. AUXILIARY EQUIPMENT: 3,000# valve fitted to drill
pipe.

8. TESTING, LOGGING AND CORING PROGRAM:

Samples:	None
DST'S:	None anticipated
Logging:	None
Coring:	None

NO. OF PAGES 3	DEPT: S. J. M. S. W. FAX # 885-9264
	FROM: S. J. M. S. W. PHONE: 623-6036
	FAX # 622-3811
	CO: 1188-222

***** F A X T R A N S M I T T A L M E M O *****

10: BLM
DEPT: S. J. M. S. W. FAX # 885-9264
FROM: S. J. M. S. W. PHONE: 623-6036
FAX # 622-3811
CO: 1188-222

Post-It Brand fax transmittal memo 7671