

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Roger C. Hanks</i>		Lease <i>Judy Conn.</i>		Well # <i>1</i>	
Location of Well	Unit <i>1980sve</i>	Section <i>7</i>	Township <i>19</i>	Range <i>25</i>	County <i>Eddy</i>
Drilling Contractor	<i>McVey Drilling Co</i>		Type of Equipment <i>Rotary to start approx. 6-30-75</i>		
* witness APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2</i>	<i>13 7/8"</i>	<i>72</i>		<i>400</i>	<i>200 cin.</i>
* <i>11"</i>	<i>8 7/8"</i>	<i>32</i>		<i>1100</i>	<i>600 "</i>
<i>7 7/8"</i>	<i>4 1/2"</i>	<i>10.5+11.6</i>		<i>9400</i>	<i>150 +</i>
Casing Data: <i>13.50 K.B. TO G.L.</i>					
Surface _____ joints of _____ inch # Grade _____ (Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole _____ Size of Casing <i>2 1/2"</i> Sacks cement required <i>2800</i>					
Type of Shoe used <i>GUIDE</i> Float collar used <i>INSERT</i> Btm 3 jts welded <i>THREADED</i>					
TD of hole <i>1100</i> Set <i>1112</i> Feet of <i>5 1/2</i> Inch <i>2 1/2</i> # Grade <i>1112</i>					
New-used csg. @ <i>1100</i> with <i>150</i> sacks neat cement around shoe <i>1112</i>					
+ <i>100</i> sax <i>40000</i> additives <i>5 1/2</i> sacks <i>1112</i>					
Plug down @ <i>12 15</i> (AM) (PM) Date <i>7-7-75</i>					
Cement circulated <i>NO</i> No. of Sacks _____					
Cemented by _____ Witnessed by <i>Len Boyette</i>					
Temp. Survey ran @ _____ (AM) (PM) Date <i>7-7-75</i> top cement @ <i>150</i>					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					

TAG REPORT @ 440' NEW HOBBS TEG.

STAGE #1. 416' - 35 SX CLASS C, 3% GEL, 4% CaCl₂ IN PLACE @ 8 15 AM 7-7-75. (TAG INT @ 384)
STAGE #2. 352' - 30 SX CLASS C, 3% GEL, 4% CaCl₂ IN PLACE @ 10 30 AM 7-7-75 (NO FILL)
STAGE #3. 352' - 30 " " " " " " @ 12 30 PM 7-7-75 (TAG INT @ 320)
STAGE #4. 320' - 160 SX CLASS C, 2% CaCl₂ IN PLACE @ 3 30 PM 7-7-75 (CIRC SET 25 SX TO G.L.)