

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 25471

RECEIVED

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

MAR 27 1980

7. UNIT AGREEMENT NAME

O. C. D.

8. FARM OR LEASE NAME

Artesia, Office

Seven Rivers Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

North Cemetery (Wolfcamp)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 17, T-20-S, R-25-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

FEB 4 1980

2. NAME OF OPERATOR

DAVID FASKEN

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

3. ADDRESS OF OPERATOR

608 First National Bank Building, Midland, TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

Unit C, 660' FNL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3533' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-18-80 - Rigged up casing pulling & well plugging equipment1-19-80 - Pulled 226 jts 2-3/8" N-80 4.60#/ft NU Buttress thread tubing & 4 1/2" x 2-3/8" packer. Set C.I.B.P. @ 7100' & dumped 2 sx cement on top of C.I.B.P. SDON.1-21-80 - Ran in well w/226 jts 2-3/8" tbg (6935') & displaced well fluid w/10#/gal salt water mud. Pulled out of hole & laid down 106 jts 2-3/8" tbg & stood back in doubles 120 jts tbg. SDON.1-23-80 - Stripped & dug out cellar, removed BOP's & tbg head, welded pull nipple on 4 1/2" csg. Removed 4 1/2" csg slips, rigged up hydraulic jacks & free pointed csg @ 5650'. Cut off csg @ 5696' w/jet cutter. Laid down pull joint. SDON.1-24-80 - Spotted 65 sx Class "C" cement plug through 4 1/2" csg up from 5669'. Laid down 127 jts 4 1/2" 11.60#/ft K-55 LT&C csg (4264'). SDON.1-25-80 - Laid down 43 jts 4 1/2" 11.60#/ft K-55 LT&C csg (1396'). Ran in well w/tbg & spotted 40 sx Class "C" cement @ 3623'. Laid down 43 jts tbg & spotted 50 sx Class "C" cement @ 2320'. Laid down 28 jts tbg & spotted 80 sx Class "C" cement @ 1450'. Pulled tbg & SDON.

(Continued on reverse side)

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert H. Angevine

TITLE

Robert H. Angevine, Agent

DATE

2-1-80

(This space for Federal or State office use)

ACTING DISTRICT ENGINEER

APPROVED BY (Offg. Eng.) GEORGE H. STEWART

TITLE

DATE

MAR 28 1980

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Posted
ID 2
3 28 80
P4A

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO 680-379

(Continuation from front)

1-26-80 - Ran in well w/tbg & tagged cement @ 1235'. Pulled out of hole & laid down tbg, cut off 13-3/8" braden head, set 5 sx cement plug @ surface, installed dry hole marker, rigged down plugging unit, moved all surface equipment to yard.

1-29-80 - Levelled pit & ripped pad.