DISTRIBUTION SANTA FE FILE U.S.G.S. Form C-103 Supersedes Old C-102 and C-103 Effective 1-1-65 RECEIVE Sa. Indicate Type of Lease
SANTAFE NEW MEXICO OIL CONSERVATION COMMISSION C-102 and C-103 Effective 1-1-65
SANTAFE NEW MEXICO OIL CONSERVATION COMMISSION Effective 1-1-65
FILE '
DEPELVE The teleplant Time of the control of the co
U.S.G.S. RELIE VE 131. Indicate Type of Lease
LAND OFFICE State K Fee
5 State Oil & Gas Lease No.
NOV 25 1975 E 5136
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR
1. OSE PAPPLICATION FOR PERMIT 20 (FORM C-101) FOR SUCH PROPOSALS.) 7. Unit Agreement Name
OIL GAS [V]
WELL LA OTHER- 2. Name of Operator 8. Form or Lease Name
DEPCO, Inc. / DHY State
3. Address of Operator 9. Well No.
800 Central, Odessa, Texas 79761
4. Location of Well
UNIT LETTER F 1980 FEET FROM THE North LINE AND 1980 FEET FROM Wildcat
THE West LINE, SECTION 23 TOWNSHIP 19S RANGE 28E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 12. County
11111111111111111111111111111111111111
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ALTERING CASING ALTERING CASING
TEMPORARILY ABANDON COMMENCE DRILLING OPNS. A PLUG AND ABANDONMENT
PULL OR ALTER CASING CASING TEST AND CEMENT JOB A
OTHER
OTHER
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed
work) SEE RULE 1 103.
77 4 75
11-4-75 Spudded 12:00 P.M. 11-4-75. Drilled 17 1/2" hole to 417', ran 12 3/4" 31#
casing set at 417. Cemented with 200 sx. Lodense w/2% ca. cl., 5# Gilsonit
& 4# Flocele per sack. Followed w/200 sx. Class C w/2% ca. cl. Cement
circulated. Plug down 2:10 P.M. 11-5-75.
11-5-75 WOC 18 hrs. Installed BOP & tested BOP and casing to 700#. OK.
11-12-75 Drilled 11" hole to 2800'. Ran 20 jts. 8 5/8" 28# and 48 jts. 8 5/8" 24#
casing set at 2800'. Cemented w/921 sx. Class C 2% Lodense w/5# Gilsonite
& 1/4# Celo flakes. Followed w/200 sx. Class C w/2% Ca. Cl. Plug down
2:00 A.M. 11-12-75. Top of cement at 541 on temperature survey. WOC 22 hrs
Resumed drilling. Tested casing @ 2000# for 30 minutes. OK.
Resumed diffing. Tested easing & 2000% for your minutes. OR.
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.
D. R. Mason TITLE Chief Clerk DATE 11-18-75

SUPERVISOR, DISTRICT I

DATE NOV 25 1975

CONDITIONS OF APPROVAL, IF ANY: