

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	9724	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	9980	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	10,280	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss Morrow	10,810	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian Miss	11,472	T. Menefee	T. Madison
T. Queen	T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya		T. Mancos	T. McCracken
T. San Andres	T. Simpson	2690	T. Gallup	T. Ignacio Qtzte
T. Glorieta	T. McKee	4255	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger		T. Dakota	T.
T. Blinbry	T. Gr. Wash		T. Morrison	T.
T. Tubb	T. Granite		T. Todilto	T.
T. Drinkard	T. Delaware Sand		T. Entrada	T.
T. Abo	T. Bone Springs		T. Wingate	T.
T. Wolfcamp	T.	8815	T. Chinle	T.
T. Penn.	T.		T. Permian	T.
T. Cisco (Bough C)	T.	9454	T. Penn. "A"	T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	700	700	Red bed & surface				
700	950	250	Red bed & sand				
950	1380	430	Anyh & Salt				
1380	2301	921	Anhy				
2301	3602	1301	Lime				
3602	3749	147	Sand & shale				
3749	5181	1432	Lime & shale				
5181	5618	437	Lime				
5618	8888	3270	Lime & shale				
8888	9100	212	Lime shale, sand				
9100	10,742	1642	Lime, shale				
10,742	10,853	111	Lime, shale, chert				
10,853	11,040	187	Lime, shale				
11,040	11,200	160	Lime, shale, sand				
11,200	11,553	353	Lime, shale				
			DST Details Attached				