

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

NOV 19 1976

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator MONSANTO COMPANY	8. Farm or Lease Name COVERT COM.
3. Address of Operator 1330 Midland National Bank Tower, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>6</u> TOWNSHIP <u>20S</u> RANGE <u>25E</u> NMPM.	10. Field and Pool, or Wildcat Dagger Draw Morrow Gas
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <u>Spud</u> <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1f03.

Spudded 9:00 AM 11/14/76.

Drilled 17½" hole to total depth of 400'.
Set 13 3/8" 48# H-40 ST&C new casing at 400' & cemented to surface w/ 350 Sx.
lite & 150 Sx. Class "C" w/ 2% CaCl.

Plug down 12:00 noon 11/17/76

WOC 24 Hrs & tested w/ 1000 psi for 30 Mins., held OK

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

W. A. Gressett

TITLE Regional Prod. Mgr.

DATE 11/18/76

APPROVED BY

W. A. Gressett

TITLE SUPERVISOR, DISTRICT II

DATE NOV 19 1976

CONDITIONS OF APPROVAL, IF ANY: