

UNITED STATES **N. M. O. C. C. COPY**
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
(Other Instructions on Reverse Side)Copy to SF
Form approved
Budget Bureau No. 42 11424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | | |
|---|--|--|
| 1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER | | 5. LEASE DESIGNATION AND SERIAL NO. NM 662 |
| 2. NAME OF OPERATOR Yates Petroleum Corporation | | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| 3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, NM 88210 | | 7. UNIT AGREEMENT NAME |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FSL & 1980' FEL of Sec. 19-20S-25E | | 8. FARM OR LEASE NAME Federal "FC" |
| 14. PERMIT NO. | | 9. WELL NO. 1 |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3541' GR | | 10. FIELD AND POOL, OR WILDCAT Cemetery |
| | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 19-20S-25E Unit 0 NMPM |
| | | 12. COUNTY OR PARISH Eddy |
| | | 13. STATE NM |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 17½" hole at 10:30 AM 11-26-75.

TD 250'. Ran 6 joints of 13-3/8" 48# K-55 (255') set at 250' KB. Cemented w/125 sacks of Halli-lite, 5# gil 1/2# flocele 4% CaCl + 85 sacks of Class C 4% CaCl. PD 9:00 PM 11-26-75. Cement circulated. WOC 12 hours and drilled cement, reduced hole to 12¼" and resumed drilling.

TD-3254'. Ran 74 joints of 8-5/8" 24# K-55 ST&C (3260') of new casing, w/Guide shoe. insert float at 3204', 4 centralizers and 2 baskets at 1008 and 911'. Cemented w/1000 sacks of Halli-lite 2% CaCl + 150 sacks of Class "C" 2% CaCl. PD 2:00 AM 12-8-75. WOC 18 hours, cut off landing joint, nipples up and installed BOP's, tested to 1000#, OK. Drilled cement plug and tested shoe to 600#, OK. Reduced hole to 7-7/8" and resumed drilling.

RECEIVED

DEC 16 1975

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Thompson

TITLE

Geol. Secty

DATE

12-14-75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

DEC 19 1975

*See Instructions on Reverse Side

O. C. C.
ARTESIA, OFFICE