

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instructi
verse side)CATE*
on re-Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 662

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different level.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ FEB 4 19762. NAME OF OPERATOR
Yates Petroleum Corporation ✓3. ADDRESS OF OPERATOR
207 South 4th Street - Artesia, NM 882104. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface 660' FSL & 1980' FEL of Section 19-20S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3541' GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal "FC"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT
Cemetery11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA
Sec 19-20S-25E
Unit 10 NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Set Production Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

TD 9715'; PBTD 9596' (WLTD). Ran 52 joints of 5½" 17# N-80 LT&C (2161'), 27 joints of 5½" 17# K-L (1330'), 109 joints of 5½" 15.5# K-55 LT&C (4442') and 47 joints 5½" 17# N-80 (1786') (Total 9719') set at 9700' KB. 1-Guide shoe, diff-fill float collar at 9658' KB. 8 centralizers at 9617', 9492', 9323, 7703, 7578, 7137, 7006, 6865. Cemented w/500 gallons of mud flush and 275 sacks of Class "H" 1/2% CFR-2, 5# KCL + 225 sacks of Hal-lite 1/2% CFR-2, 5# KCL + 80 sacks Class "H" 1/2% CFR-2, 5# KCL, displaced w/40 bbls 2% KCL + 187 bbls fresh water. PD 11:45 AM 1-9-76. Bumped plug and set slips w/2000#. WOC and ran wireline, found top of cement at 6140'.

RECEIVED
FEB 2 1976
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Johnson

TITLE

Geol. Secty

DATE

2-2-76

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

APPROVED
FEB 3 1976
L. L. BECKWITH
ACTING DISTRICT ENGINEER