

UNITED STATES **Artesia, NM 88210**

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

C/SF

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR

Yates Petroleum Corporation/

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660/S 1980/E, Sec. 19-20S-25E

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Perforate

SUBSEQUENT REPORT OF:

**RECEIVED**  
MAR - 9 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE

NM 662

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

**RECEIVED**

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal FC

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat Canyon

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit 0, Sec. 19-T20S-R25E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3556' KB

**APR 5 1982**

**O. C. D.**

ARTESIA, NM

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Load hole and pull tubing, packer and RBP. WIH and perforated 7427-39' w/10 .50" holes as follows: 7427, 28, 29, 31, 32, 33, 34½, 36, 37½ and 39'. WIH and perforated 7487-7504' w/10 .50" holes as follows: 7487, 88, 89, 90, 91, 97, 99, 7500½, 02 and 04'. RIH w/tubing, packer and RBP, straddle and treat 7427-39' w/2500 gallons 15% Spearhead HCL acid and 8 ball sealers. Acidized 7487-7504' w/2500 gallons 15% Spearhead HCL acid and 8 ball sealers. Swab back load. WIH and perforated 7074-90' w/10 .50"holes as follows: 7074, 76½, 79, 81, 82, 83, 84, 85, 88 and 90'. Acidized perforations 7074-90' w/2500 gallons 15% DS-30 HCL acid. RBP set at 7650' and packer at 7046. Well returned to production.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineering Secty

DATE

3-8-82

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

PETER W. CHESTER

MAR 25 1982

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side