NO. OF COPIES RECEIVED						(-)(t) = (-)	
DISTRBUTION						Supersedes (1) C-102 and C-164	
SANTA F .		NEW ME	XICO OIL CONSE	ERVATION CO	MMISSION	E fins tive parts	
FILE							
U.S.G.S.				RE	CEIVED	Auto de l'emergia d'ignation	_
LAND FICE					·		
OPE OR	• •			1/			
				JF	AN 20 1976		
(DO NOT USE THIS FOI USE	SUNDR	Y NOTICES AND	REPORTS ON DEEPEN OF DUG BA	PROPOSALS.)	0. с. с.		
	<u>×</u>	OTHER-		AR'	TESIA, OFFICE	7. Unit Agrees and Longe	
Yates Petroleum Corporation						Foster "FF"	Com
3. Address of Operator							
207 So. 4th Street - Artesia, NM 88210						1	
4. Location of Well	4th 5t	Lieet - Alt	esia, MM	00210		L L L L L L L L L L L L L L L L L L L	
	9	980	South	-	1980		1
UNIT LETTER	,	FEET FROM	THE DOULI	LINE AND	FEET PROV	Undesignated	1101100
East		1	20S		24E	VIII	
THEL	INE, SECTIO	N T(OWNSHIP	RANGE		Mill and	
15, Elevation (Show whether DF, RT, GE, etc.)						$\frac{1}{12.000} = \frac{1}{12.000} = \frac{1}$	(1111)
((((((((((((((((((((((((((((((((((((3583			Eddy	(AAAA)
			To Indicate N	ature of Not	ice support or Of		• · · · · · · · · · · · · · · · · · · ·
NOTIC	CE OF IN	TENTION TO:			SUBSED ON	n astronom e	
PERFORM REMEDIAL WORK]	PLUG	AND ABANDON	REMEDIAL WOR-			
TEMPORARILY ABANDON	1			COMMENCE IT	2 . TT		NN .
PULL OR ALTER CASING]	CHAN	GE PLANS	CASING TELT AN	a da ser e XX		
			,	CTH28			
OTHER		<u> </u>	i				
17. Describe Proposed or Co	mpleted Op	erations (Clearly stat	e all pertinent acta	ils, and ever to			

work) SEE RULE 1103.

Spudded a $17\frac{1}{2}$ " hole at 4 PM 12-19-75.

TD 249' - Ran 8 joints of 13-3/8" 48# K-55 new casing (249') set at 249'. Cemented w/200 sacks of Class "C" 4% CaCl. PD 6 AM 12-20-75. WOC 12 hours, drilled plug, reduced hole to 12¼" and resumed drilling. TD 1059' - Ran 24 joints of 8-5/8" 24# K-55 casing (1061.17') set at 1059' KB. 1-Tex Pattern Shoe, centralizer at 1019 & basket at 589'. Cemented with HOWCO. 500 sacks lite w/5#/sx gilsonite, 1/4# flocele and 2% CaCl. Followed w/100 sacks Class "C" + 2% CaCl. PD at 2 PM 12-23-75. Cement circulated. WOC 18 hours, nippled up, installed BOP's, tested to 1000#. OK. Drilled shoe and tested to 600#. OK. Reduced hole to 7-7/8" and resumed drilling.

18. I hereby certify that the information above is true and complete to the co	
signer Geol. Secty	1-15-76
APPROVED BY U. A. SUPERVISOR. DISTRICT I	DATE IAN 9 1 1976

CONDITIONS OF APPROVAL, IF ANY: