

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND	FICE
OPER	OR

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

MAR 30 1976

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Well State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Form of Lease Name Moore "FQ"
9. Well No. 1
10. Field, Loc., or Well Name Cemetery Morrow
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well Oil <input type="checkbox"/> GAS <input checked="" type="checkbox"/> WELL OTHER-
2. Name of Operator Yates Petroleum Corporation
3. Address of Operator 207 South 4th Street - Artesia, NM 88210
4. Location of Well UNIT LETTER <u>F</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>19</u> TOWNSHIP <u>20S</u> RANGE <u>25E</u> N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.) 3562' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	OTHER <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>
CASING TEST AND CEMENT <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, times, etc.)

Spudded a 17½" hole at 2:30 PM 3-17-76.
TD 201'. Ran 5 joints of 13-3/8" casing, 54# H-40 (201.70') set at 201'
KB. Cemented by Halliburton w/150 sacks of Class "C" 4% CaCl. PD 9:30
PM 3-17-76. Cement did not circulate. WOC 4 hours and filled hole w/3
yards of Ready-Mix. WOC 12 hours, cut off casing and nipped up, drilled
plug and reduced hole to 12¼" and resumed drilling.
TD 2200'. Ran 57 joints of 8-5/8" LT&C 32# J-55 (2203.09') of casing
set at 2200'. Cement w/700 sacks of Lo-dense w/5# per sack gilsonite,
w/1/4# flocele 2% CaCl., followed by 150 sacks of Class C 2% CaCl. *Am. 35 SA*
WOC 18 hours, nipped up, installed BOP's and tested to 1000#. OK. Drilled
plug (60' of cement) and tested to 600#. OK. Reduced hole to 7-7/8"
and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Imensen TITLE Geol. Secty DATE 3-29-76

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE MAR 30 1976

CONDITIONS OF APPROVAL, IF ANY: