

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-21755

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER Recompletion ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter F : 1980 Feet From The North O.C. Dine and 1980 Feet From The West Line
Section 19 Township 20S Range 25E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3562' GR

7. Lease Name or Unit Agreement Name

Moore FQ

8. Well No.
1

9. Pool name or Wildcat
Undesignated Strawn

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Perforate, Treat, Recomplete ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Due to considerable pressure in the Atoka zone (with very low volume) decision was made to temporarily abandon Atoka with RBP set at 7280' and tested to 1000 psi, OK.
Tested casing and found hole between 4720-4751'. Remainder of casing tested to 1000 psi, OK.
Set retainer at 4657'. Cemented w/85 bbls fresh water, 350 sx Halliburton Lite and 100 sx Class C with 5# Salt. Displaced and pulled out of retainer. Reversed hole clean.
Drilled cement retainer at 4657' and 100' cement. Circulated clean. Tested hole to 1000 psi, OK.
Perforated 8683-8760 1/2' w/10 .45" holes as follows: 8683-86' (4 holes) and 8757 1/2-60 1/2' (6 holes-2 SPF). Acidized perfs 8683-8760 1/2' w/3000 gals 15% NEFE acid. Perforated 8276-8397' w/10 .42" holes as follows: 8276-78' (3 holes), 8373-76' and 8394-97' (7 holes). Acidized perfs 8276-8397' w/2000 gals acid.
Well cleaned up and flowed 650 psi on 5/64" choke = 100 mcfpd.
Work began 12-14-88 - completed 1-17-89. Well returned to production 1-18-89.

Post ID-2
2-3-89
P+ A Ato.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 1-20-89

TYPE OR PRINT NAME Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

Original Signed By
Mike Williams

JAN 20 1989

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: