

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	2
LAND OFFICE	1
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

MAY 19 1976

O.C.C.  
ARTESIA OFFICE

30-015-21817  
Form C-101  
Revised 1-1-65

## APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work b. Type of Well OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> SINGLE ZONE <input type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator David Fasken ✓		8. Farm or Lease Name Howell State Comm.	
3. Address of Operator 608 First National Bank Bldg., Midland, Texas 79701		9. Well No. 1	
4. Location of Well UNIT LETTER L LOCATED 660 FEET FROM THE West LINE AND 1980 FEET FROM THE South LINE OF SEC. 32 TWP. 20-S R. 25-E N.M.P.M.		10. Field and Pool, or Wildcat Cemetery (Morrow)	
11. Elevation (Show whether DE, RT, etc.) 3677.5' Gr.		12. County Eddy	
21A. Kind & Status Plug Bond Statewide		20. Rotary or C.C. Rotary	
21B. Drilling Contractor Warton Drilling Co.		22. Approx. Date when will start May 22, 1976	

23.

## PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17-1/2"	13-3/8"	48#	200'	200	Surface
12-1/4"	8-5/8"	24# & 32#	3000'	1100	Surface
7-7/8"	4-1/2"	11.6#	9900'	450	7000'

Proposed drilling program --- please see attachment.

This gas is dedicated to Natural Gas Pipeline Co. of America.

APPROVAL VALID  
FOR 90 DAYS UNLESS  
DRILLING COMMENCED,

EXPIRES 8-21-76

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Robert H. Angevine Title Agent Date May 18, 1976

(This space for State Use)

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE MAY 21 1976

CONDITIONS OF APPROVAL, IF ANY:

Cement must be circulated to  
surface behind 13 3/8" & 8 5/8" casing

Notify N.M.O.C.C. in sufficient  
time to witness cementing  
8 5/8"