

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on reverse side)Form approved,  
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 1358

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C Tank Unit Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREASec. 12-20S-23E  
Unit J NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 4th Street - Artesia, NM 88210 O.C.C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1650' FSL &amp; 1980' FEL of Section 12-20S-23E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3990' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 9080'; PBTD 6773'. - The Cisco was perforated at 6659-6708', acidized and tested; swabbed and flowed gas and salt water after clean up. A blanking plug was set in the packers and the Basal Abo was perforated at 5004-5085', acidized and tested; swabbed sulfur water with show of gas behind each swab.

We propose to plug and abandon the well as follows: (1) Retrieve tubing and packers; (2) Set CIBP at 6600' w/35' of cement on top of plug; (3) Shoot off casing at about 4200' and spot 35 sacks of cement across casing stub; (4) spot 35 sacks of cement plug at 2550-2450'; (5) Spot 35 sacks at 1870-1770'; 35 sacks at 960-860'; install a temporary marker.

RECEIVED

DEC 22 1976

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineer

DATE 12-21-76

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE DEC 23 1976

CONDITIONS OF APPROVAL, IF ANY: