

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JUN 15 1979

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fed & Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator

Roger C. Hanks ✓

3. Address of Operator

P. O. Box 3148, Midland, Texas 79702

4. Location of Well

UNIT LETTER P, 990 FEET FROM THE South LINE AND 990 FEET FROM

THE East LINE, SECTION 13 TOWNSHIP 19 S RANGE 24 E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Molly Com

9. Well No.

#1

10. Field and Pool, or Wildcat

N. Dagger Draw Upper Penn

15. Elevation (Show whether DF, RT, GR, etc.)

3606.4 GR

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

PLUG AND ABANDON ☒

CHANGE PLANS ☐

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1105. 13 3/4" - 402 - 300 8 7/8" - 1115 - 750 5 1/2" - 8020 - 280

The operator has had no experience in plugging and abandoning wells in this area, however, it is the intent of the operator to adequately plug and abandon the subject well in accordance with OCC regulations. A typical summary of the anticipated procedures is listed below.

(Actual footage will be supplied as work progresses.)

Bridge plug + 100' plug over perforations at 7676'

100' plug at the stub (in & out) tag

100' plug at the top of the Glorieta; anticipated at approximately 2300' 1850-1950

100' plug (in & out) at the base of the intermediate casing, 8-5/8", anticipated at 1115' 1065-1165 + tag

10' plug at the surface with appropriate marker

Clean and grade location

Note: There will be no intermediate or surface casing pulled on this well since cement was circulated on both strings during drilling operations.

24 hour notice will be given to OCC before setting bottom plug.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Roger C. Hanks TITLE Owner-Operator DATE 6/13/79

APPROVED BY W. A. Gussett TITLE SUPERVISOR, DISTRICT II DATE JUN 19 1979

CONDITIONS OF APPROVAL, IF ANY:

1. Plug at 3950-4050

Notify N.M.O.C.C. in sufficient time to witness

Plugging