

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
AUG 16 1976

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
K6260

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR INFORMATION CONCERNING A WELL OR FIELD OR A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL C-103 FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator C. E. LaRue and B. N. Muncy, Jr.	8. Form or Lease Name P. V. State
3. Address of Operator P. O. Box 196 Artesia, New Mexico 88210	9. Well No. 1
4. Location of Well UNIT LETTER R 990 FEET FROM THE South LINE AND 430 FEET FROM THE East LINE, SECTION 16 TOWNSHIP 19S RANGE 26E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3252.5 GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 10 3/4" Casing at 374' and circulated cement with 85 sacks. Set 7" Casing at 920' and cemented with 350 sacks class C with 2% CaCl, and 1/4# cellophane flakes and 5# Kolite per sack, followed with 100 sacks Class C with 2% CaCl. Ran temperature survey and found cement top at 790', ran 1" to 790' and used 50 sacks Class C with 2% CaCl, waited 3 hours tagged bottom at 651' and used 200 sacks with 2% CaCl to circulate.

Spud Date: July 28, Cemented surface: July 29, Drilled out from under Surface: July 31, Cemented intermediate: August 1, Finished cementing through 1": August 2.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Operator DATE August 2, 1976

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: