

UNITED STATES OF AMERICA
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR MONSANTO COMPANY

3. ADDRESS OF OPERATOR 1330 Midland National Bank Tower, Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State or Federal Survey or Area. See also space 17 below.)
At surface 660' FSL & 1980' FEL Sec. 32, T-19S, R-25E, Eddy Co., New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
GL 3503

5. LEASE DESIGNATION AND SERIAL NO.
NM 18959

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
ALBERT FEDERAL COM.

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Dagger Draw

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 32, T-19S, R-25E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>	WATER SHUT-OFF	<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	FRACTURE TREATMENT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	SHOOTING OR ACIDIZING	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	(Other) Spud	<input type="checkbox"/>
(Other)	<input type="checkbox"/>	(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 17½" hole 3:00 AM 11/5/76.
Drilled 17½" hole to total depth of 395' & set 13 3/8" 48# H-40 ST&C Casing at 395' & cemented to surface w/ 350 Sx. Lite w/ ½# Flocele & 5# Kolite/Sx., 2% CaCl & 150 Sx. Class "C", 2% CaCl; Plug down 6:30 PM 11/6/76.
WOC 24 Hrs & tested w/ 1000 psi for 30 Mins; Held OK.

Drilled 12½" hole to total depth of 1374' and set 9 5/8" 36# K-55 LT&C Casing at 1374' & cemented to the surface w/ 600 Sx. Lite, 5# Koalite, ½# Cello/ Sx., 2% CaCl & 200 Sx. Class "C" plus 2% CaCl; Plug down 3:15 AM 11/10/76.
WOC 24 Hrs & tested w/ 1500 psi for 30 Mins., held OK.

RECEIVED

NOV 12 1976

U S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED W. M. Behall TITLE Regional Production Mgr. DATE 11/11/76

(This space for Federal or State office use)

APPROVED BY Joe S. Lara TITLE ACTING DISTRICT ENGINEER DATE NOV 16 1976

CONDITIONS OF APPROVAL, IF ANY: