Submit 3 Copies
To Appropriate

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised March 25, 1999

DISTRICT I	OH CONCEDE/ADD	ON DIVICION	WELL API NO.
DISTRICT 1 1625 N. French Dr., Hobbs, NM 88240 OIL CONSERVATION DIVISION 2040 South Pacheco		30-015 <del>-21989-</del> 1 2177	
DISTRICT II Santa Fe, NM 87505 811 South First, Artesia NM 88210		5. Indicate Type of Lease	
DISTRICT III		STATE FEE 6. State Oil & Gas Lease No.	
1000 Rio Brazos Rd., Aztec, NM 87410			
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS A. DOOLEY			
1. Type of Well: Oil Well ☐ Gas Well	☐ Other		
2. Name of Operator			8. Well No. # 1
3. Address of Operator	TRO. VORP.		<u>#</u>
5. Address of Operator			9. Pool name or Wildcat
4. Well Location			
Unit letter UT D :	300 feet from the	N line and	feet from the W line
Section 4	Township	19 <b>Range</b> 28	NMPM EDDY County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)			
Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	☐ ALTERING CASING ☐
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLIN	G OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AND C	
OTHER:		OTHER:	
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any			
proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
7/10/2000 (DOCTOR A) (TREATS 25 0/07/1 25 5			
7/18/2000 SPOTTED 40sx CEMENT AT 2425'. WOC AND TAGGED TOP OF CEMENT PLUG AT 2242'. SPOTTED 30sx CEMENT PLUG AT 2054'. SPOTTED 30sx CEMENT PLUG AT 1690'.			
7/19/2000 PERFORATED CASING AT 716'. SQUEEZED 60sx CEMENT. WOC AND TAGGED TOP OF CEMENT			
AT 599'.			
7/20/2000' PERFORATED CASING AT 285' SQUEEZED 50sx CEMENT. WOC AND TAGGED TOP OF CEMENT AT 192'.			
spotted 63 sx CEMENT FROM 192' to SURFACE.			
	RKER AND CLEARED LOCATI		
			•
	•		
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE MIKE STUBBLEF	IELD TITLE	FIELD REP. 2	DATE 10/3/2000
Type or print name  Telephone No.			
(This space for State use)			
APPROVED BY TTER & (STUPP)	· 00	REIL ROOT	DATE 12 /2400
APPROVED BY The Stull Conditions of approval, if any:	111L	E Field Rep. II	DATE 12/76/2000