

Submit 3 Copies
To Appropriate

District Office

DISTRICT I

1625 N. French Dr., Hobbs, NM 88240

DISTRICT II

811 South First, Artesia NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

Form C-103
Revised March 20, 1999

WELL API NO.

30-011-21989

5. Indicate Type of Lease

STATE ☐

FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

A. DOOLEY

8. Well No.

#1

9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

Oil Well ☐

Gas Well ☐

Other

2. Name of Operator

MESA PETRO. VORP.

3. Address of Operator

105 S 4th St.

Artesia NM 88210

4. Well Location

Unit letter UT D : 300 feet from the N line and 1120 feet from the W line

Section 4

Township 19

Range 28

NMPM

EDDY

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/18/2000 SPOTTED 40sx CEMENT AT 2425'. WOC AND TAGGED TOP OF CEMENT PLUG AT 2242'. SPOTTED 30sx CEMENT PLUG AT 2054'. SPOTTED 30sx CEMENT PLUG AT 1690'.
7/19/2000 PERFORATED CASING AT 716'. SQUEEZED 60sx CEMENT. WOC AND TAGGED TOP OF CEMENT AT 599'.
7/20/2000 PERFORATED CASING AT 285' SQUEEZED 50sx CEMENT. WOC AND TAGGED TOP OF CEMENT AT 192'.
spotted 63 sx CEMENT FROM 192' to SURFACE.
ERECTED DRYHOLE MARKER AND CLEARED LOCATION.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE MIKE STUBBLEFIELD TITLE FIELD REP. 2 DATE 10/3/2000

Type or print name

Telephone No.

(This space for State use)

APPROVED BY Mike Stubblefield TITLE Field Rep. II DATE 12/26/2000
Conditions of approval, if any: