

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	/
FILE	/ ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

JAN 17 1978

D. C. C.
ARTESIA OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-6596

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - II" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name State "HA"
3. Address of Operator 207 South 4th Street - Artesia, NM 88210.	9. Well No. 1 1
4. Location of Well UNIT LETTER 0 , 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 2 TOWNSHIP 19S RANGE 28E NMPM.	10. Field and Pool, or Wildcat Und Artesia Grayburg
15. Elevation (Show whether DF, RT, GR, etc.) 3433' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER Set Production casing <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 2852'. Ran 71 joints of 5½" 14# K-55 casing (2852') set at 2852'. 1-
float shoe at 2852'. Centralizers at 2814, 2694, 2574, 2444, 2325, 2204, 2084'
Cemented w/600 sacks of 50/50 poz + 2% gel tailed in w/150 sacks of Class C
3# KCL + 0.5% D-65 displaced w/180 bbls of water. Cement circulated.
PD 3:35 PM 6-19-77.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 1-16-78

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JAN 19 1978

CONDITIONS OF APPROVAL, IF ANY: