Corry to SF

Form 9-331 (May 1963)

UNITED STATES DEPARTMENT OF THE INTERIOR

SUBMIT IN TRIF CATE*
(Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424. EASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY			LC-029392B	LC-029392B		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such properties. The properties of the properties of the properties of the properties.			6. IF INDIAN, ALLOTTEE (OR TRIBE NAME		
1. OIL GAS GAS	HER	ALE A AND	7. UNIT AGREEMENT NAM	D.		
2. NAME OF OPERATOR Honeysuckle Explor	ation Corporation	MU2 0 1317	8. FARM OR LEASE NAME Federal 26			
3. ADDRESS OF OPERATOR 1610 North J. Mid		ARVESIA. UFFICE	9. WELL NO.			
4. LOCATION OF WELL (Report lo See also space 17 below.) At surface	ation clearly and in accordance with a	ny State requirements.*	10. FIELD AND POOL, OR Shugart			
2310' FNL & 1980'	PEL /		11. SEC., T., R., M., OR BLI SURVET OR AREA Sec. 26. T-18:	s, R31E		
14. PERMIT NO.	15. ELEVATIONS (Show whether	DF, RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE		
	3657.8'	GR	Eddy	N. Mex.		

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON*		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	REPAIRING WELL ALTERING CASING ABANDONMENT*	X.
REPAIR WELL (Other)		CHANGE PLANS		(Other) (NOTE: Report results of mul- Completion or Recompletion R	tiple completion on Well eport and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.)*

Set bridge plug @ 3955' shutting off previous perfs. (4028'- 47' & 4045'- 47'). Perforated 3674'- 82', 3705'- 07' & 3734'- 37' w/2 jet shots/ft. Fraced these perfs w/60,000 gals. of fluid, 51,500# of 10/20 sand & 10,000# of 100 mesh sand.

Set retrievable bridge plug @ 3192'. Perforated 2642'- 52', 2666', 2670', 2700'- 02', 2709'- 11', 2754' & 2764' w/2 jet shots/ft. Fraced these perfs w/29,000 gals. of fluid, 6000# 100 mesh sand & 22,600# of 10/20 sand.

RECEIVED

JUL 28 1917

J. S. GEOLOGICAL MEN MENTO

18. I hereby certify that the foregoing is true and correct SIGNED Collaboration	TITLE Agent	DATE	7/26/77
(This space for Federal of State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	ACTING DISTRICT ENGINEER	DATE	AUG 1 - 1977