

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-28015

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Eddy "D" Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

North Shugart Atoka

North Shugart Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 20-18S-31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

P.O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1980' FNL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3633' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Ran int. csg & cmt

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Reached TD of 12½" hole @ 4505' @ 9A, 6-18-79. Ran 9-5/8" csg*, set @ 4505' w/DV @1035'. Cmt w/1600 sx lite w/½# Floseal & 2% CaCl₂ & 200 sx Class "H" w/2% CaCl₂. Circulated 300 sx. Open DV tool cmt 2/100 sx Class "C" neat. WOC over 18 hours. Tstd BOPs to 5000#; csg to 2000# - held OK. Started drlg 8-3/4" hole @ 4505'. (* 10 jts 9-5/8" 40# N80 LT&C csg - 404'; 101 jts 9-5/8" 40# J55 LT&C csg - 4060'.)

Work performed 6-18-79 to 6-19-79.

RECEIVED

JUN 21 1979

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

R.L. Vaughn

TITLE Area Drilling Supt.

DATE 6-20-79

(This space for Federal or State-office use)

APPROVED BY

J. E. Gillham

TITLE

ACTING DISTRICT ENGINEER

DATE

JUN 21 1979

CONDITIONS OF APPROVAL, IF ANY: