

Lease KOOHANE C. et al Fed.

Well No. 1

Pool Morrow - Atoka

Location 1980 FSL 1990 FWL Sec 21-185-31E

County Eddy

State NM

D/C

AFF 53923

GLE: 3650'

KDB:

H = 1815'

New Well Completion

Initial Comp. Date: _____

Producing Formation: _____

Zone	Comp. Date	Date Aband

13 3/8" H-40, 48#
CSG @ 626' cmt. circ.

9 7/8" OD 40 # Grade 5-95 N 80' K-55

Treatment History: (Current Zone)

Set @ 4505' w/ _____ sxs

Top of Cmt @ Circ. by:

2 3/8" H.7# N-80 8rd th

2 3/8" H.7# N-80 CS Hybrid

Notes Cmt. plug pumped
down w/ snash 2% KCL
water + United Chemical's
C-70 corrosion inhibitor

SN w/ 1.87" protile

Otis RDH Dual packer @ apx. 11,100' ±

SN w/ 1.87" protile

See VANN TOOL'S DIAGRAM FOR
details below packer.

Proposed ATOKA PERFS
11,174'-84' w/ 2-JHPF

2 3/8" H.7# N-80 CS Hybrid
between packers

Otis ON-OFF tool w/ 1.87" protile

Otis PERMA-LATCH packer @ apx 11,500' ±

See VANN TOOL'S DIAGRAM FOR DETAILS
below packer.

Proposed MORROW PERFS
11,572'-80' & 11,657'-80'
w/ 2-JHPF

Producing History:

Formation: _____

Month or Year	Oil	Wtr	Gas

Last Test Dated: _____

BOPD _____

BWPD _____

MCF _____

FL: _____

Calc. Ppg. Eff: _____

Cum. Oil _____

Cum. Gas _____

7" OD 23 1/2 # Grade 11-80' K-55

Remarks and Recommendation:

Set @ 11,923' w/ 750 sxs

Top of Cmt @ 2700' by TS

* CSG. bottom up.

- 3947' 7" N-80 26#
- 2291' 7" K-55 26#
- 2436' 7" K-55 23#
- 203' 7" N-80 23#
- 2074' 7" K-55 26#
- 964' 7" N-80 26#

Notes Otis RDH Dual packer normally
short string safety can be released by
either string w/ 2000# wtl. Both LS155 1-1-1

Prepared By: R. Worley

Date: 9-7-70