

MOCC COPY,

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

copy to SF  
Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ GAS ☒ OTHER ☐  
WELL WELL

RECEIVED

2. NAME OF OPERATOR

JUN 24 1977

Gulf Oil Corporation

North Shugart Deep Well Unit

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240 O. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with State requirements.\*  
See also space 17 below.)  
At surface

660' FNL & 2180' FEL, Section 29, 18-S, 31-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5. LEASE DESIGNATION AND SERIAL NO.

LC-029387-C (KC)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undes Atoka Morrow

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 29, 18-S, 31-E

12. COUNTY OR PARISH 13. STATE

Eddy New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

McVay Drilling Company spudded 17-1/2" hole at 10:00 AM, June 16, 1977. Drilled to 620'. Ran 13-3/8" casing set and cemented at 620' with 315 sacks of Class C with 6% gel, 2% Ca Cl2 and 200 sacks of Class C with 2% Ca Cl2. Cement circulated. WOC 18 hours. Tested casing with 600#, 30 minutes, OK.

Started drilling 12-1/4" hole at 620'.

RECEIVED

JUN 22 1977

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED D. F. Berlin

TITLE Area Engineer

DATE June 20, 1977

(This space for Federal or State office use)

APPROVED BY Joe S. Lara  
CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE JUN 23 1977