

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029387-C

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

GULF OIL CORPORATION

3. ADDRESS OF OPERATOR

P.O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)  
At surface

660' FNL &amp; 2180' FEL

7. UNIT AGREEMENT NAME

No. Shugart Deep

8. FARM OR LEASE NAME

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Bone Springs

11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA

Sec. 29-T18S-R31E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3622' GL

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7331' PB. 12,000' TD. POH w/2-7/8" tbg & pkr. Set CIBP @ 7050'. Circ hole w/abandonment mud. Cap CIBP w/35' cmt & test to 1000#. Cut 7" csg @ 6200' & POH. Set cmt plug from 6250' to 6150' - 50' in csg & 50' on top of cut csg. Set cmt plug from 4865' to 4765' - 50' in 9-5/8" csg & 50' below csg in open hole. Set 50' cmt surf plug. Install dry hole marker; clean & clear location.

RECEIVED

OCT 22 1979

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

H. B. Sikes, Jr.

TITLE Area Engineer

DATE 10-18-79

(This space for Federal or State office use)

APPROVED BY

GEORGE H. STEWART

TITLE

ACTING DISTRICT ENGINEER

DATE OCT 26 1979

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side