

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

OCT 21 1977

O. O. C.

ASCEIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
K 6096

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator MONSANTO COMPANY	8. Farm or Lease Name Albert State Com.
3. Address of Operator 1330 Midland NBT, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER F 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 19S RANGE 25E NMPM.	10. Field and Pool, or Wildcat Cemetery Morrow Und.
15. Elevation (Show whether DF, RT, GR, etc.) Gr. 3511	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 8 3/4" hole to 9628'; dry hole; verbal approval to plug and abandon as follows obtained from Mr. W. A. Gressett.

Cement Plugs as follows:

9586 - 9486	40 Sx.
9110 - 9020	40 Sx.
8300 - 8200	40 Sx.
7700 - 7600	40 Sx.
5900 - 5800	40 Sx.
3600 - 3500	40 Sx.
2250 - 2150	40 Sx.
1450 - 1350	50 Sx.
10' Surface	10 Sx.

Hole between plugs will be filled with better than 25% Gel per bbl water; 4" pipe marker with location thereon will be set at surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. A. Gressett TITLE Regional Prod. Mgr. DATE 10/20/77

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE OCT 21 1977

CONDITIONS OF APPROVAL, IF ANY: