

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

SEP 13 1977

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDY NOTICES AND REPORTS OF WELLS
100 NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101, FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Amoco Production Company

3. Address of Operator
P. O. Drawer A, Levelland, Texas 79336

4. Location of Well
UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE East LINE, SECTION 6 TOWNSHIP 19-S RANGE 29-E NMPM.

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
L-2653

7. Unit Agreement Name

8. Farm or Lease Name
State "ER" Com

9. Well No.
1

10. Field and Pool, or Wildcat
Und. Turkey Track Morrow

12. County
Eddy

15. Elevation (Show whether DF, RT, GR, etc.)
3413.5 RDB

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	
		OTHER ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 8-13-77 Marcum Drilling Co. spudded 17½" hole at 9:30 PM. Drilled to a TD of 418' and set 13 3/8" casing at 418'. Cement with 400 sx Class "C" cement. Plug down at 4:30 PM 8-14-77 and circulate 47 sx cement to surface. WOC 25 hrs. Test casing with 800# for 30 min. Test ok. Reduce hole to 12¼" and resume drilling at 9:00 PM 8-15-77.

Reached TD of 3665' 8-24-77. Run 9 5/8" casing and set at 3665'. Cement with 1950 sx Halliburton Lite cmt + additives and 200 sx Class "C" cement. Plug down at 6:00 PM 8-24-77 with 1800 PSI. Circ 400 sx cement. WOC 30 hrs. Test casing with 1500# for 30 min. Test ok. Reduce hole to 8 3/4" and resume drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ray W. Cox TITLE Administrative Assistant DATE 9-12-77

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE SEP 13 1977

CONDITIONS OF APPROVAL, IF ANY:
013 NMOC - ART, 1-Div., 1-Susp., 1-Northern Natural, 1-RC