

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 100
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Monsanto Co.</i>		License <i>Lakewood State Com.</i>		Well # <i>1</i>	
Location of Well	Unit <i>F</i> <i>1980NW</i>	Section <i>30</i>	Township <i>19</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor	<i>KK A</i>		Type of Equipment <i>Rotary & Start gear. 8-5-77</i>		

* *Witness*

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2"</i>	<i>13 3/8"</i>	<i>48</i>		<i>500</i>	<i>500 Cms.</i>
* <i>12 1/4"</i>	<i>9 5/8"</i>	<i>36</i>		<i>1400</i>	<i>800 "</i>
<i>8 3/4"</i>	<i>5 1/2"</i>	<i>20</i>		<i>9600</i>	<i>1200</i>

Casing Data:

Surface *35* joints of *1 1/2* inch *26* # Grade *255*

☒ (Approved) (Rejected)

Inspected by *John P.* date *8/11/77*

Cementing Program

Size of hole *12 1/4* Size of Casing *9 5/8* Sacks cement required *750*

Type of Shoe used *Shoe* Float collar used *low* Bim 3 jts welded *Yes*

TD of hole *1400* Set *40* Feet of *1 1/2* inch *26* # Grade *255*

New/used csg. @ *400* with *750* sacks neat cement around shoe *0.5-1.2*

+ *500* sacks *100* additives *10# 5.6 min 4# 2.8 min 2# 1.6 min 1# 0.8 min*

Plug down @ *1100* (AM) (PM) Date *8/12/77*

Cement circulated *40* No. of Sacks *15*

Cemented by *John P.* Witnessed by *John P.*

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: *Test OK*