

SANITARY		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Oil and Gas
Effective 1-1-65

AMENDED C-103

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

L-3854

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM AND PROCEED TO LIST OR TO CHECK OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE THIS APPLICATION FOR REPORT ON OTHER CASES, FOR A DIFFERENT RESERVOIR.)

RECEIVED

OIL WELL ☐ GAS WELL ☐ OTHER: Dry hole

7. Name of Operator

Southland Royalty Company

JAN 19 1978

7. Unit Agreement Name

-

8. Form or Lease Name

Stuart-State Comm.

9. Address of Operator

1100 Wall Towers West, Midland, TX 79701

O. C. C.

MEDIA. OFFICE

9. Well No.

1

4. Location of Well

UNIT LETTER B 660 FEET FROM THE north LINE AND 1980 FEET FROM

THE east LINE, SECTION 1 TOWNSHIP 19-S RANGE 27-E NMPM.

10. Field and Pool, or Wildcat
Undesig. - Illinois Camp
(Morrow)

15. Elevation (Show whether DF, RT, GR, etc.)

3533.0' GR

12. County

Eddy

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐REMEDIAL WORK ☐ALTERING CASING ☐TEMPORARILY ABANDON ☐COMMENCE DRILLING OPNS. ☐PLUG AND ABANDONMENT ☒PULL OR ALTER CASING ☐CHANGE PLANS ☐CASING TEST AND CEMENT JOG ☐OTHER ☐OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

AMENDED C-103 to replace C-103 dated 1-11-78 to show additional cement plug 3808-4000'.

12-28-77 TD 10,590'; PBTD 8730'. Rigged up Permian Basin Casing Pullers. POH w/tbg.

Set CI Bridge Plug @ 8150'. Spotted 3 sx cement in 4 1/2" casing 8115-8150'. Shot casing @ 6295', 6000', 5500', casing free at 5500'.

12-30-77 Recovered 5500' of 4 1/2" casing. Ran 2 3/8" tbg., spotted 60 sx cement 5176-5529' in top of 4 1/2" casing and 7 7/8" hole.

12-31-77 Tagged cement w/tbg @ 5176'. Spotted 60 sx cement via 2 3/8" tbg @ 3808-4000'. Spotted 60 sx cement via 2 3/8" tbg @ 2260-2500'. Spotted 30 sx cement via 2 3/8" tbg @ 2260-2500'. Spotted 30 sx cement 355-475', 10 sx cement @ surface. Removed wellhead, welded plate over casing. Installed dry hole marker. Hole filled w/10.0# gal mud.

WELL PLUGGED AND ABANDONED 12-31-77.

1-17-78
P-15
2-3

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

C. Harvey Carr

TITLE

District Engineer

DATE 1-17-78

APPROVED BY

TITLE

DATE

SIGNATURES OF APPROVAL, IF ANY