

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANITARY	/
FILE	/
U.S.G.S.	/
LAND OFFICE	/
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

AMENDED C-103

SUNDARY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR ANY OTHER PURPOSES OR FOR ANY OTHER PERSONS.

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER Dry hole

2. Name of Operator
Southland Royalty Company

3. Address of Operator
1100 Wall Towers West, Midland, TX 79701

4. Location of Well
WELL LETTER B 660 FEET FROM THE north LINE AND 1980 FEET FROM
east LINE, SECTION 1 TOWNSHIP 19-S RANGE 27-E N.M.P.M.

5. Elevation (Show whether B.F., RT, GR, etc.)
3533.0' GR

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
L-3854

7. Unit Agreement No.
-

8. Form of Lease Name
Stuart-State Comm.

9. Well No.
1

10. Field and Pool, or well, at
Undesig. -- Illinois Camp (Morrow)

12. County
Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

AMENDED C-103 to replace C-103 dated 1-11-78 to show additional cement plug 3508-4000'.

12-28-77 TD 10,590'; PBTD 8730'. Rigged up Permian Basin Casing Pullers. POH w/tbg.

12-29-77 Set CI Bridge Plug @ 8150'. Spotted 3 sx cement in 4½" casing 8115-8150'. Shot casing @ 6295', 6000', 5500', casing free at 5500'.

12-30-77 Recovered 5500' of 4½" casing. Ran 2 3/8" tbg., spotted 60 sx cement 5176-5529' in top of 4½" casing and 7 7/8" hole.

12-31-77 Tagged cement w/tbg @ 5176'. Spotted 60 sx cement via 2 3/8" tbg @ 3808-4000'. Spotted 60 sx cement via 2 3/8" tbg @ 2260-2500'. ~~Spotted 30 sx cement via 2 3/8" tbg @ 2260-2500'.~~ Spotted 30 sx cement 355-475', 10 sx cement @ surface. Removed wellhead, welded plate over casing. Installed dry hole marker. Hole filled w/10.0# gal mud.

WELL PLUGGED AND ABANDONED 12-31-77.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. Harvey Carr TITLE District Engineer DATE 1-17-78

OFFICED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE MAR - 2 1978

CONDITIONS OF APPROVAL, IF ANY: