

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Marbet Energy Corp</i>		Lease <i>Mack Draw</i>			Well # <i>1</i>
Location of Well	Unit <i>1980s+e</i>	Section <i>2</i>	Township <i>19</i>	Range <i>26</i>	County <i>Eddy</i>
Drilling Contractor	<i>Pennsylvania Drilling Co</i>		Type of Equipment <i>Rotary to start 9-9-77</i>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>10</i>	<i>7"</i>	<i>20</i>		<i>920</i>	<i>Circ</i>
<i>6 1/4</i>	<i>4 1/2</i>	<i>10.5</i>		<i>1250</i>	<i>Circ.</i>

Casing Data:

Surface 24 joints of 7 inch 20 # Grade APT New K-55
(Approved) (Rejected)

Inspected by *Susan Gilman* date 9-12-77

Cementing Program

Size of hole 9 1/2 Size of Casing 7 Sacks cement required 310

Type of Shoe used Guide Float collar used Insert Btm 2 jts welded

TD of hole 925 GL Set 925 GL Feet of 7 Inch 20 # Grade K-55

New-used csg. @ 925 GL with 125 sacks neat cement around shoe Class C 28 cc
+ 1.85/sax Herculite additives 5" Gilsonite 1/4" Tloc 2% cc

Plug down @ 5120 (AM) (PM) Date 9-12-77

Cement circulated Yes No. of Sacks 36/50

Cemented by Halliburton Witnessed by Susan Gilman

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: