

NMOCC COPY  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE  
(Other instructions on  
reverse side)

Form approved  
Budget Bureau No. 42-R1424.

Copy to SF

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

**RECEIVED**

OIL WELL ☒ GAS WELL ☐ OTHER ☐

NAME OF OPERATOR

Shenandoah Oil Corporation

ADDRESS OF OPERATOR

1500 Commerce Building - Fort Worth, Texas

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

Unit Letter "H" - 1650' FNL and 330' FEL  
Section 30 - 18S - 3TE

5. LEASE DESIGNATION AND SERIAL NO.

LC 029387 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Shugart "D"

9. WELL NO.

11

10. FIELD AND POOL, OR WILDCAT

Shugart Y-SR-Q-G

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 30-T18S-R31E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

4. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3619 Gr.

### 6. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Casing Report

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12-29-77

Drilled 11" hole to 771'. Ran 19 jts of new 8-5/8" 23# and set @ 758'.  
Cemented w/250 sx Halliburton Lite cement with 1/4# Flow Seal and 5#  
gilsonite per sk. Also cemented with 100 sx Class "C" with 2% CaCl.  
Circulated 75 sx.

1-5-78

Ran and set 97 jts of new 5-1/2" 14# J-55 @ 3840' Gr. Level. Cemented  
with 900 sx of Halliburton Lite with 1/4# Flow Seal and 5# gilsonite  
and 10# salt per sk. Also ran 385 sx of Class "H" with .5 of 1% CFR-2  
and 3# salt and 10# sand per sk. Top of cement: 1580'.

**RECEIVED**  
JAN 25 1978  
U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. W. Downey, Jr.

TITLE Mgr.-W. Texas-New Mexico Div. DATE Jan. 23, 1978

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT ENGINEER

DATE JAN 26 1978