

NMOCC COPY

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029387 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Shugart "D"

9. WELL NO.

12

10. FIELD AND POOL, OR WILDCAT

Shugart 4-SR-Q-66

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 30-T18S-R31E

12. COUNTY OR PARISH

Eddy

13. STATE  
New Mexico1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Shenandoah Oil Corporation ✓

3. ADDRESS OF OPERATOR

P. O. Box 4534 - Odessa, Texas 79760

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

Unit "F"

2310' FWL &amp; 1650' FNL - Sec. 30-18S-31E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3614 GR

O. C. C.

ARTESIA, OFFICE

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

Casing Report

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Drilled 11" hole to 740'. Ran 19 jts. new 8-5/8" 24# - H. 40 casing. Set @ 728' GR. level. Cemented w/250 Sx. Halliburton Lite Cement w/1/4# Flo-Seal and 100 Sx. Class "C" w/2% CaCl. Cement did not circulate. In six hours, ran 1" pipe to top of cement @ 580' and cement w/100 Sx. Class "C" w/4% CaCl. Circulated to surface.

2. Ran new 5 1/2" - 14# - K-55 to T.D. Set @ 3,839' w/D. V. Tool @ 1,940'. Cemented first stage w/485 Sx. Class "H" w/.5 of 1% CFR<sub>2</sub> - 5# Salt & 10# Sand per Sk.

Cemented 2nd stage thru D. V. Tool w/845 Sx. Halliburton Lite w/5# gilsonite, 1/4# Flo-seal & 18# salt per Sk.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Mrg., W-Texas-New Mexico Div DATE May 22, 1978

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE MAY 31 1978

CONDITIONS OF APPROVAL, IF ANY: