

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

APR 6 1978

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-55

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L 5098	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Texas Oil & Gas Corp.		8. Farm or Lease Name Indian Hills State Com.
3. Address of Operator 900 Wilco Building, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>G</u> , <u>1650'</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>20S</u> RANGE <u>24E</u> N.M.P.M.		10. Field and Pool, or Wildcat Undesignated (Morrow)
15. Elevation (Show whether DF, RT, GR, etc.) 3604.8 G. R.		12. County Eddy

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
☐

SUBSEQUENT REPORT OF:

REMEDIATION WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/19/78 Spud 17 1/2" hole @ 11:30 A.M.

3/20/78 Finish 17 1/2" hole to 400'. Ran 10 jts. 13 3/8", 48#, H-40, ST&C casing to 400'. Cement with 225 sxs. 50/50 Poz. "C" followed by 200 sxs "C" w/2% CaCl₂. Cement circulated to surface. WOC. Cut off and nipped up BOP.

3/21/78 Drilled out with 12 1/4" bit using fresh water.

3/27/78 Finished 12 1/4" hole to 3,000'. Ran 2300' of 8 5/8", 24#, K-55, ST&C and 700' 8 5/8", 32#, K-55, ST&C casing set at 3000'. Cement with 975 sxs. 50/50 Poz. "C" with 6% gel, 1/4#/sx. flocele, 2% CaCl₂ followed by 200 sxs "C" with 2% CaCl₂. Cement circulated to surface. WOC. Cut off and nipple up BOP. Test BOP to 3000#-O.K.

3/28/78 Drilled out with 7 7/8" bit using fresh water.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED S. P. Baker TITLE Dist. Drlg. Engr. DATE April 4, 1978

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: