

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

JAN 18 1979

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-2632
7. Unit Agreement Name
8. Farm or Lease Name Pecos River State
9. Well No. 1
10. Field and Pool, or Wildcat McMillan 7-Rivers Queen
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator McClellan Oil Corporation ✓
3. Address of Operator P. O. Box 848, Roswell, New Mexico 88201
4. Location of Well UNIT LETTER <u>K</u> <u>2110</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>19-S</u> RANGE <u>27-E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3341.4 G. L.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1/15/79: Pursuant to verbal instructions, this test will be plugged as follows: Place 45sx cement @ total depth 20' plug at the surface and heavy mud between plugs. Install dry hole marker and restore surface to as near normal as possible.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Jack J. McClellan</u>	TITLE <u>Operator</u>	DATE <u>1/15/79</u>
APPROVED BY <u>W. A. Gussert</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>JAN 19 1979</u>

CONDITIONS OF APPROVAL, IF ANY: