

STATE	COUNTY	ELEVATION	McClellan	COMPANY	
New Mexico	Eddy	3341 G.L.	12/78	McClellan Oil Corporation	
DATE OF SAMPLES	LOCATION	S	T	R	FARM
ble Tool	2110' ESL & 1650' FWL	32	19-S	27-E	Pecos River State
					WELL NO. 1

DEPTH	DOLO	LIME	DESCRIPTION	SALT	ANHY	SHALE	SAND	CHT.	NOTES
%	%	%	%	%	%	Red Gry. Grn. Blk.	Red Gry. Description	%	
			Originally drilled O-370 by Road Stevens No sample description available (Sand villa log)						
70-72			Poor sample - Gravel plug back material						
78					100				
* 81	100		Tan fx. oil stn on fracture				Oil odor - tight		Good gold fluv. -
86	20		Tan fx tight N.S.		80				
90	50		" " Tr. oil stn		50	Cx			Gold fluv.
95	10		" "		90				
400	10		" "		70			20	Gry highly shaly sd. N.S.
05	10				60			30	" " "
10	100		Tan dn. dolo.						all gold fluv.
15	50				30			20	fg friable to shaly silt
20	50		Tan fx		50				
26	50		Tan fx - Good stn in 20%		50	Water?	Oil odor - Intex		pos?
			Making 2 barrels water/hr. - Leaking from 8 7/8" csg?						
35	50		Tan fx to sucrose		50				
40	70		" 20% w/ppp		30				Sema stn.
54	100		Tan dn to massive						
62	70		Tan fx to sucrose		30				
73	80		" "		20				
77	80		" "		20				
84	20		" "		80				
89	20				80				
91	10				90				
			T.D. 491' - Carrying too much water to drill with P.A. 1/15/79						

RECEIVED

JAN 22 1979

D. C. C.
ARTESIA, OFFICE

