

UNITED STATES GEOLOGICAL SURVEY  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYCOPY  
SUBMIT IN TRIPlicate  
(Other instructions on  
reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 14118

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Yates, Fed. # 6 Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated Morrow

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

21-19-24

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Drawer "A", Levelland, TX 79336

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface

660' FNL X 660' FEL Sec. 21 (Unit A, NE $\frac{1}{4}$  NE $\frac{1}{4}$ )O. C. C.  
ARTESIA, OFFICE

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3700.2 GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Spud. Surface csg.

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MGF Drilling Co. Rig No. 23 spudded a 17 $\frac{1}{2}$ " hole at 12:15 P.M. 3-8-78. Reached TD of 217' 3-9-78. Ran 13-3/8" 48# H-40 ST&C casing and set at 217'. Cement with 250 sx Class C + 2% CACL. Plugged down 2:35 A.M. 3-9-78. Circulated 24 sx to surface. WOC 20 hours. Test casing w/350# for 30 minutes. Test ok. Reduced hole to 12 $\frac{1}{4}$ " and resumed drilling.

RECEIVED  
APR 10 1978  
U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray W. Cox

TITLE

Administrative Supervisor

DATE

3-29-78

(This space for Federal or State office use)

APPROVED BY

J. L. Lara

TITLE

ACTING DISTRICT ENGINEER

DATE

APR 11 1978

CONDITIONS OF APPROVAL, IF ANY:

- 0 & 4 - USGS, A  
1 - Div.  
1 - Susp.  
1 - RC

\*See Instructions on Reverse Side