

LAKEWOOD STATE NO. 1
1980' FSL & FWL, Sec. 25, T.19S, R.27E
Eddy County, New Mexico

CURRENT

GL-3462'
KB-3478'

WELL SCHEMATIC	CASING	SIZE	WEIGHT	GRADE	THREAD	DEPTH	
			13 3/8	48 #		ST&C	425'
	CASING	8 5/8	24 & 32 #	K-55	ST&C	3000'	
	TUBING	4 1/2	14.6 & 13.5 #	N-80		11,150'	
	TUBING						
	DESCRIPTION OF EQUIPMENT						DEPTH
	13 3/8" casing, 450 sx Class C cmt. to surface						425'
	8 5/8" casing, 1200 sx Halliburton Lite cmt. to surface						3,000'
	T.O.C. @ 8660'						
	Perfs: 10,175'-10,181' (Atoka)						
	Top of cement plug - 10,490'						
	CIBP @ 10,500' w/ 10' cmt. on top						
	Perfs: 10,583'-10,750' (Upper Morrow)						
	CIBP @ 10,775'						
	Perfs: 10,791'-10,948' (Lower Morrow)						
	4 1/2" casing, 725 sx Class H, (PBD 11,091')						11,150'
	PREPARED BY						DATE
	Stephen A. Kneeger						5-25-90