

LAKEWOOD STATE NO. 1

1980' FSL & FWL Sec. 25, T19S, R27E

Eddy County, New Mexico

PROPOSED

GL-3462

KB-3478

WELL SCHEMATIC

CASING	SIZE	WEIGHT	GRADE	THREAD	DEPTH
	13 3/8	48		ST&C	425'
CASING	8 5/8	24 & 32#	K-55	ST&C	3000'
TUBING	4 1/2	16.6 & 15.5#	N-80		11,150'
TUBING					

DESCRIPTION OF EQUIPMENT

DEPTH

Surface plug (10 sx)

13 3/8" casing, 450 sx Class C cmt. to surface

425'

Cement plug 475'-375' (40 sx)

MUD LADEN FLUID

Cement plug 3050'-2950' (40 sx)

8 5/8" casing, 1200 sx Halliburton Lite cmt. to surface

3,000'

100' in & out cmt. plug @ 4 1/2" csg. stub

T.O.C. @ 8660'

10 sx cmt. plug on top of CIBP
CIBP @ 10,100'

Perfs: 10,175'-10,181' (Atoka)

Top of cement plug - 10,490'

CIBP @ 10,500' w/ 10' cmt. on top

Perfs: 10,583'-10,750' (Upper Morrow)

CIBP @ 10,775'

Perfs: 10,791'-10,948' (Lower Morrow)

4 1/2" casing, 725 sx Class H (POTD 11,091')

11,150'

PREPARED BY

Stephen A. Rinegar

DATE

5-25-90